

MOVINCOOL®

THE #1 PORTABLE SPOT COOLING SOLUTION

OFFICE PRO® 10

OP 10

- 110-volt-compatible
- 9,600 Btu/h, ETL-Verified
- Fully integrated air exhaust system
- Plant Engineering's Product of the Year
- Complete 24/7 programmability

PC 7

- Compact, portable and fully self-contained
- Ideal for localized hot spots
- 6,800 Btu/h, ETL-Verified
- Ultra-low power consumption
- Whisper-quiet performance





Technical Specs		PC 7	Office Pro® 10
Electronic Features	Control Panel	Programmable	Programmable
	Thermostat Control	Electronic	Electronic
Cooling Capacity	Rating Conditions	6,800 Btu/h*	9,600 Btu/h**
Electrical	Voltage Requirement	1 Phase, 115V	1 Phase, 115V
Characteristics	Total Power Consumption	0.93 kW	1.25 kW
	Current Consumption	8.4 amps	11.5 amps
	Recommended Fuse Size	15 amps	15 amps
	NEMA Plug Configuration	5-15	5-15
	Min. - Max. Voltage	105-125	105-125
Fans	Motor Output - high/low	0.09 kW/NA	0.08/0.05 kW Evap 0.19 kW Cond
Evaporator	Fan Type	Centrifugal	Impeller
	Max. Air Flow - high/low	178 CFM/NA	205/175 CFM
	Max. External Static Pressure	NA	0.27 IWG
Condenser	Fan Type	Centrifugal	Impeller
	Max. Air Flow	NA	370 CFM
	Max. External Static Pressure	NA	0.52 IWG
Compressor	Type	Hermetic Rotary	Hermetic Rotary
	Output	0.84 kW	0.68 kW
R-22 Charge		1.24 lb	1.61 lb
Dimensions	W x D x H	15 x 18 x 33 in	22 x 14 x 38 in
Net Weight / Shipping Weight		84/90 lb	130/172 lb
Power Cord	Gauge	14 AWG (3-core)	14 AWG (3-core)
	Length	6 ft	6 ft
Condensate Tank Capacity		1.5 gal	2.4 gal
Operating Conditions	Min. - Max. (@ 50% RH)	65°- 85°F	65°- 95°F
Max. Duct Length	Per Cold Duct Hose	NA	NA
	Hot Duct Hose	6.5 ft	25 ft
Max. Sound Level	With Condenser Duct - high/low	51 dB/NA	58/51 dB
	Without Condenser Duct - high/low	NA/NA	60/53 dB
	*Rating Conditions: 80°F at 50% RH		
	**Rating Conditions: 95°F at 60% RH		